blueparrott GN

BlueParrott M300-XT

ENGINEERED TO KEEP YOU CONNECTED ON THE GO.

Our smallest and lightest Bluetooth® headset with 80% noise-cancellation.

- > 80% noise-cancellation with 2-mic tech
- > Just 20g for all day comfort
- > IP54-rated protection against dust and > Customisable BlueParrott Button™
- > Up to 14 hours of talk-time
- > Up to 100m wireless range



| Audio | Noise reduction on calls | Yes |
|-----------------|------------------------------------|--|
| | Speaker size | 10.3mm 0.41in |
| | Speaker max input power | 5 mW |
| | Speaker frequency range | 20Hz |
| | Speaker impedance | 32 Ω |
| | Audio codecs supported | SBC |
| | Microphone type | 2 x MEMS |
| | Microphone sensitivity | -42±1dB (0dB=1V/Pa, at 1KHz) |
| | Certifications and compliance | FCC, ISED, CE, RoHS, REACH, Proposition 65 |
| Fit & comfort | Headset form factor | BT Mono |
| | - EarGels | Large, Medium, Small |
| Connectivity | Connectivity | Bluetooth |
| | Bluetooth profiles | A2DP v1.3, HFP v1.7, HSP v1.2 |
| | Bluetooth version | 5.1 |
| | Operating range (Bluetooth) | Up to 100m 300ft |
| | Bluetooth pairing list | Up to 8 Bluetooth devices |
| | Simultaneous Bluetooth connections | 2 |
| | NFC (Near Field Communication) | Yes |
| Battery | Talk-time | Up to 14 hours |
| | Corded charging (cable dependent) | USB-C™ |
| | Charging time | Up to 150 minutes |
| | Standby time | Up to 420 hours |
| | Battery type | Rechargeable lithium-ion battery |
| Software & Apps | Compatible software and apps | BlueParrott App, BlueParrott Updater |
| | Over-the-air firmware updates | Yes |

| TECHNICAL SPECIFICATIONS | | | | |
|--------------------------|------------------------------|--|--|--|
| General info | Box contents | Headset, 3 sets of EarGels™, User documents, USB cable | | |
| | Packaging dimensions (WxHxD) | 41.5mm x 175mm x 131mm 1.63in x 6.89in x 5.16in | | |
| | Main unit dimensions (WxHxD) | 110.7mm x 61mm x 25.4mm 4.36in x 2.4in x 1in | | |
| | Weight | 20g 0.7oz | | |
| | USB cable length | 1.2m 3.9ft | | |
| | IP rating (main unit) | IP54 | | |
| | Warranty | 2 years | | |
| Extended info | Operating temperature | -10°C to 60°C 14°F to 140°F | | |
| | Storage temperature | -10°C to 45°C 14°F to 113°F | | |

| PRODUCT TYPE | SKU | DESCRIPTION |
|--------------|--------|-----------------------------------|
| Products | 204347 | BlueParrott M300-XT |
| Accessories | 204354 | BlueParrott M300-XT Refresher Kit |